

Real-Tite, Inc
Real-Tite® Plugs
2525 Nevada Ave, North #307
Minneapolis, MN 55427
Phone: 952-938-0600 Fax: 952-938-0692
800-877-0610



Standards and Specifications for 3.5 Inch Countersunk Chrome Hex Extension Real-Tite® Expansion Plug– Standard RTPCX35

MATERIALS:

Real-Tite® Plugs are constructed of a 6" 22GA Chrome cover, hard ABS Plastic for the components, ASTM SC-715 Neoprene for the gasket and a Stainless Steel ¼ -20 x 1 ¾" male-female Standoff stop bolt and square nut.

At a relaxed position the 3.5 inch Countersunk Chrome Hex Extension Plug fits an ID of 3.82" (95mm) and fully expanded seals openings up to 4.15" (101mm) ID. The OD of the cover is 4.78". The overall length of the plug at a relaxed state is 3.75" The Counter Sunk screw requires a 5/32 hex key to tighten and loosen and provides a flush tamper proof finish.

USES:

Real-Tite® Plugs have a variety of uses including clean outs, test plugs, sealing iron or plastic damaged pipe with threaded or smooth openings.

ADVANTAGES:

Real-Tite® Plugs are designed with a stop on the bolt, to prevent the lower wedge from becoming dis-assembled from the unit and dropped down the line.

Real-Tite® Plugs have an extremely large gasket that seals behind, over and at the tip of the pipe or opening.

Real-Tite® Plugs are easy to remove and can be reused saving time and money.

