

Real-Tite, Inc  
Real-Tite® Plugs  
2525 Nevada Ave, North #307  
Minneapolis, MN 55427  
Phone: 952-938-0600 Fax: 952-938-0692  
800-877-0610



## Standards and Specifications for 4.0 Inch Thumb Bolt Real-Tite® Expansion Plug—Standard RTPTB40

### **MATERIALS:**

Real-Tite® Plugs are constructed of hard ABS Plastic for the components, Black Santoprene 101-64 for the gasket and a Stainless Steel ¼ -20 x 2" Thumb stop bolt and square nut.

At a relaxed position the 4.0 inch Thumb Bolt Plug fits an ID of 4.20" (107mm) and fully expanded seals openings up to 4.61" (117 mm) ID. The OD of the cover is 4.0". The overall length of the plug at a relaxed state is 3.40". The Thumb Bolt screw is used to tighten and loosen the plug.

### **USES:**

Real-Tite® Plugs have a variety of uses including clean outs, test plugs, sealing iron or plastic damaged pipe with threaded or smooth openings.

### **ADVANTAGES:**

Real-Tite® Plugs are designed with a stop on the bolt, to prevent the lower wedge from becoming dis-assembled from the unit and dropped down the line.

Real-Tite® Plugs have an extremely large gasket that seals behind, over and at the tip of the pipe or opening.

Real-Tite® Plugs are easy to remove and can be reused saving time and money.

